



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	G	L1	L2	L3	L4	ΦD1	ΦD2	↻
APX04-G01	4	G1/8	5.5	11	43	14.5	11.5	3.2	14
APX04-G02	4	G1/4	7.5	11	45.5	14.5	11.5	3.2	17
APX04-G03	4	G3/8	7.5	11	46	14.5	11.5	3.2	20
APX06-G01	6	G1/8	5.5	13	44	15	13.5	3.2	14
APX06-G02	6	G1/4	7.5	13	46.5	15	13.5	3.2	17
APX06-G03	6	G3/8	7.5	13	47	15	13.5	3.2	20
APX06-G04	6	G1/2	10	13	49.5	15	13.5	3.2	24
APX08-G01	8	G1/8	5.5	15	46.3	18	15	3.2	14
APX08-G02	8	G1/4	7.5	15	48.8	18	15	3.2	17
APX08-G03	8	G3/8	7.5	15	49.3	18	15	3.2	20
APX08-G04	8	G1/2	10	15	51.8	18	15	3.2	24
APX10-G01	10	G1/8	5.5	18	56	21	19	4.2	17
APX10-G02	10	G1/4	7.5	18	58.5	21	19	4.2	17
APX10-G03	10	G3/8	7.5	18	58.5	21	19	4.2	20
APX10-G04	10	G1/2	10	18	62	21	19	4.2	24
APX12-G01	12	G1/8	5.5	21	59.5	21.5	21.5	4.2	21
APX12-G02	12	G1/4	7.5	21	62	21.5	21.5	4.2	21
APX12-G03	12	G3/8	7.5	21	62	21.5	21.5	4.2	21
APX12-G04	12	G1/2	10	21	65	21.5	21.5	4.2	24