



TUBE O.D	MALE PIPE THREAD	CATALOG NUMBER	C	D	M	N
3/16	1/8	72x3A	3/8	0.219	0.62	0.69
1/4	1/8	72x4A	3/8	0.219	0.63	0.72
1/4	1/4	72x4B	7/16	0.312	0.70	0.85
5/16	1/8	72x5A	7/16	0.219	0.72	0.72
5/16	1/4	72x5B	7/16	0.312	0.75	0.90
3/8	1/4	72x6A	7/16	0.312	0.78	0.88
3/8	3/8	72x6B	7/16	0.438	0.78	0.97
1/2	3/8	72x8C	5/8	0.438	0.94	1.10
1/2	1/2	72x8D	11/16	0.562	0.98	1.20
5/8	1/2	72x10D	11/16	0.562	1.06	1.31

Brass Compression Fittings

Typical application:

Instrument connection, hydraulic and pneumatic systems.

Pressure:

Working pressure up to 2000psi a 4:1 safety factor depending on tube size, When using plastic tubing, Use the working pressure for type used.

with Bundy-weld.

Temperature Range:

-65°F to +250°F

-53°C to +120°C

Used With:

copper, brass aluminum and steel hydraulic tubing.

Material:

CA360 Brass

