



Features

- *Accurate regulation of an optimal airflow rate for precise motion control.
- *The compact design provides the comparable range of speed as the larger ones do.
- *Control-out and control-in types are available for all models.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air(No other gases or liquids)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL(ΦD-T)					
Tube(Metric)-Thread(R)			Tube(Inch)-Thread(NPT)		
ASC04-M5(B)	ASC06-04(B)	ASC10-03(B)	ASC5/32-U10(B)	ASC1/4-N02(B)	ASC3/8-N01(B)
ASC04-01(B)	ASC08-01(B)	ASC10-04(B)	ASC5/32-N01(B)	ASC1/4-N03(B)	ASC3/8-N02(B)
ASC04-02(B)	ASC08-02(B)	ASC12-01(B)	ASC3/16-U10(B)	ASC1/4-N04(B)	ASC3/8-N03(B)
ASC06-M5(B)	ASC08-03(B)	ASC12-02(B)	ASC3/16-N01(B)	ASC5/16-N01(B)	ASC3/8-N04(B)
ASC06-01(B)	ASC08-04(B)	ASC12-03(B)	ASC3/16-N02(B)	ASC5/16-N02(B)	ASC1/2-N02(B)
ASC06-02(B)	ASC10-01(B)	ASC12-04(B)	ASC1/4-U10(B)	ASC5/16-N03(B)	ASC1/2-N03(B)
ASC06-03(B)	ASC10-02(B)		ASC1/4-N01(B)	ASC5/16-N04(B)	ASC1/2-N04(B)