



TUBE O.D.	CATALOG NUMBER	C	D	M
3/16	64x3	3/8	0.125	0.60
1/4	64x4	3/8	0.188	0.62
5/16	64x5	1/2	0.250	0.66
3/8	64x6	1/2	0.312	0.72
1/2	64x8	19/32	0.406	0.94
5/8	64x10	19/32	0.500	1.06
3/4	64x12	7/8	0.562	1.19
1/4x1/4x1/8	64x4x4x2	3/8	Tee is the same	
1/4x1/4x3/8	64x4x4x6	1/2		
1/4x3/8x1/4	64x4x6x4	1/2		
3/8x3/8x1/4	64x6x6x4	1/2		
1/2x1/2x1/4	64x8x8x4	19/32		
1/2x1/2x3/8	64x8x8x6	19/32		
5/8x5/8x3/8	64x10x10x6	19/32		
5/8x5/8x1/2	64x10x10x8	19/32		

Brass Compression Fittings

Typical application:

Instrument connection, hydraulic and pneumatic systems.

Pressure:

Working pressure up to 2000psi a 4:1 safety factor depending on tube size, When using plastic tubing, Use the working pressure for type used.

with Bundy-weld.

Temperature Range:

-65°F to +250°F

-53°C to +120°C

Used With:

copper, brass aluminum and steel hydraulic tubing.

Material:

CA360 Brass

