



TUBE O.D	MALE PIPE THREAD	CATALOG NUMBER	C	D	D1	L
1/8	1/8	68x2A	7/16	0.094	0.219	0.78
3/16	1/8	68x3A	7/16	0.125	0.219	0.84
1/4	1/8	68x4A	7/16	0.188	0.219	0.88
1/4	1/4	68x4B	9/16	0.188	0.312	1.06
5/16	1/8	68x5A	1/2	0.250	0.219	0.91
5/16	1/4	68x5B	9/16	0.250	0.312	1.09
3/8	1/8	68x6A	9/16	0.312	0.219	0.97
3/8	1/4	68x6B	9/16	0.312	0.312	1.17
3/8	3/8	68x6C	11/16	0.312	0.438	1.16
3/8	1/2	68x6D	7/8	0.312	0.562	1.34
1/2	1/4	68x8B	11/16	0.406	0.312	1.22
1/2	3/8	68x8C	11/16	0.406	0.438	1.22
1/2	1/2	68x8D	7/8	0.406	0.562	1.41
5/8	1/2	68x10D	7/8	0.500	0.562	1.50
3/4	1/2	68x12D	1	0.562	0.562	1.62
3/4	3/4	68x12E	1-1/16	0.562	0.750	1.62

Brass Compression Fittings

Typical application:

Instrument connection, hydraulic and pneumatic systems.

Pressure:

Working pressure up to 2000psi a 4:1 safety factor depending on tube size, When using plastic tubing, Use the working pressure for type used.

with Bundy-weld.

Temperature Range:

-65°F to +250°F

-53°C to +120°C

Used With:

copper, brass aluminum and steel hydraulic tubing.

Material:

CA360 Brass

