



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	G	G1	L1	L2	L3	L4	ΦD1	↻
APHF04-G01	4	G1/8	G1/8	5.5	8.5	29	23.5	11.5	14
APHF04-G02	4	G1/4	G1/4	7.5	11	35	25.5	11.5	17
APHF06-G01	6	G1/8	G1/8	5.5	8.5	29	23.5	13.5	14
APHF06-G02	6	G1/4	G1/4	7.5	11	35	25.4	13.5	17
APHF06-G03	6	G3/8	G3/8	7.5	12	41	29.5	13.5	21
APHF06-G04	6	G1/2	G1/2	10	14	47.5	32.5	13.5	24
APHF08-G01	8	G1/8	G1/8	5.5	8.5	29	26.5	15	14
APHF08-G02	8	G1/4	G1/4	7.5	11	35	28.9	15	17
APHF08-G03	8	G3/8	G3/8	7.5	12	41	29.8	15	21
APHF08-G04	8	G1/2	G1/2	10	14	47.5	32.5	15	24
APHF10-G01	10	G1/8	G1/8	5.5	8.5	32	30.3	19	14
APHF10-G02	10	G1/4	G1/4	7.5	11	36	32.6	19	17
APHF10-G03	10	G3/8	G3/8	7.5	12	41	33	19	21
APHF10-G04	10	G1/2	G1/2	10	14	47.5	36	19	24
APHF12-G02	12	G1/4	G1/4	7.5	11	36	33.5	21.5	17
APHF12-G03	12	G3/8	G3/8	7.5	12	41	35.5	21.5	21
APHF12-G04	12	G1/2	G1/2	10	14	47.5	36.5	21.5	24