



TUBE O.D	INVERTED MALE	CATALOG NUMBER	C	D	D1	M	N
1/8	1/8	69x2A	11/32	0.094	0.219	0.60	0.67
3/16	1/8	69x3A	11/32	0.125	0.219	0.62	0.69
1/4	1/8	69x4A	3/8	0.188	0.219	0.62	0.75
1/4	1/4	69x4B	3/8	0.188	0.312	0.62	0.75
1/4	3/8	69x4C	15/32	0.188	0.438	0.75	0.91
1/4	1/2	69x4D	9/16	0.188	0.562	0.81	1.12
5/16	1/8	69x5A	15/32	0.250	0.219	0.62	0.75
5/16	1/4	69x5B	15/32	0.250	0.312	0.69	0.84
5/16	3/8	69x5C	15/32	0.250	0.438	0.75	0.91
5/16	1/2	69x5D	9/16	0.250	0.562	0.84	1.12
3/8	1/8	69x6A	3/8	0.312	0.219	0.69	0.69
3/8	1/4	69x6B	15/32	0.312	0.312	0.75	0.94
3/8	3/8	69x6C	15/32	0.312	0.438	0.84	0.94
3/8	1/2	69x6D	9/16	0.312	0.562	0.87	1.12
7/16	1/4	69x7B	9/16	0.350	0.312	0.84	1.00
1/2	1/4	69x8B	9/16	0.406	0.312	0.84	0.94
1/2	3/8	69x8C	9/16	0.406	0.438	0.88	0.97
1/2	1/2	69x8D	19/32	0.406	0.562	0.94	1.13
1/2	3/4	69x8E	13/16	0.406	0.750	1.16	1.25
5/8	3/8	69x10C	11/16	0.500	0.438	1.06	1.12
5/8	1/2	69x10D	11/16	0.500	0.562	1.06	1.16
5/8	3/4	69x10E	13/16	0.500	0.750	1.16	1.31
3/4	1/2	69x12D	15/16	0.562	0.562	1.19	1.31
3/4	3/4	69x12E	15/16	0.562	0.750	1.19	1.38

Brass Compression Fittings

Typical application:
Instrument connection, hydraulic and
pneumatic systems.

Pressure:
Working pressure up to 2000psi a 4:1 safety
factor depending on tube size, When using
plastic tubing, Use the working
pressure for type used.
with Bundy-weld.

Temperature Range:
-65°F to +250°F
-53°C to +120°C

Used With:
copper, brass aluminum and steel hydraulic
tubing.

Material:
CA360 Brass

